


2AR3-0W-SI

Food Grade



Cover

Top Color	White
Thickness	0.01" (0.3mm)
Material	Silicone
Pattern	Glossy
Durometer	75 A

Carcass

Plies	2
Fabric	Polyester
Anti-static	Yes
Laterally Rigid	Yes
Pulley Side Material	Polyester

Weight

0.041 lbs./in.-ft. (2.4 kg/m²)

Maximum Width

66" (1.7m)

Overall Thickness

0.085" (2.2mm)

Minimum Pulley at 70°F

Min Pulley <180°	2" (50.8mm)
Min Pulley Reverse Bend	3.5" (88.9mm)

Contact Temperature Range

-65°F to 350°F (-54°C to 177°C)	
Intermittent	Contact Mol Belting

Working Tension

Minimum	26-42 lbs./in. (4.6-7.4 N/mm)
Maximum	120 lbs./in. (21 N/mm)

Elongation

0.4% @ 26 lbs./in. (4.6 N/mm)
0.7% @ 42 lbs./in. (7.4 N/mm)
2% @ 120 lbs./in. (21 N/mm)

Coefficient of Friction

Mild Steel	0.22
S/S	0.24
UHMW	0.17

Splicing/Lacing Methods

Splicing	Angle Step Splice
Lacing #1	Unibar #36 SP
Lacing #2	Alligator #1

Characteristics

FDA	Yes
Non-Marking	Yes
Flame Retardant	No
Release Characteristics	Excellent
Incline Conveying	Yes
Trough Conveying	No
Swan Neck Conveying	Good
Metal Detectors	Contact Mol Belting
(Dependent on Sensitivity)	
Chemical Resistance	See Chart

Accessories

Edgecap	No
Guide	Yes
Cleats	No
Sidewall	No
Profile	No